

Outdoor /Indoor 270X Full D1 MPEG 4 All-In-One IP High Speed Dome Camera



Specification:

Model Name	M4-727W / M4-727C
Image System	
Image Sensor	Sony 1/4" typesuperHAD CCD
Effective Pixels (HxV)	752 x 583 (NTSC), 768 x 494 (PAL)
Compression	MPEG-4 ASP hardware compression
Resolution	QCIF (160x112 in NTSC, 176x144 in PAL) CIF (352x240 in NTSC, 352x288 in PAL) Full D1 (720x480 in NTSC, 720x576 in PAL)
TV Lines	480 TV lines
Image Frame Rate	30 fps at full D1 resolution (NTSC) 25 fps at full D1 resolution (PAL)
Electric	
Sync System	Internal/ External (LineLock), auto detect
Optical Zoom	27X optical zoom, f=3.25mm(wide) to 88.0mm(tele)F1.5 to F3.8, Video AF
Digital Zoom	10X (up to 270X with optical zoom)
Focusing System	Auto (normal sensitivity/ low sensitivity)
Minimum Illumination	1 Lux (30 IRE) / 0.01 Lux with Electronic Sensitive Up
S/N Ratio	More than 48db
Tour	4 tours memorizing up to 6 mins of manual control
Iris Control	Auto / Manual
Gain Control	Auto
White Balance	Auto / Special/ Indoor / Outdoor / Manual / PushAuto
Electric Shutter	1/60~1/10000 (NTSC), 28 steps 1/50~1/10000 (PAL), 28 steps
BLC	On / Off
Auto Exposure Control	Auto / manual/ backlight compensation
Auto Exposure Compensation	-10.5 ~+10.5 dB(15 steps)
Preset	64 points
Privacy Zone	On / Off, up to 8 zones
Alarm	2 inputs/ 2 outputs
Remote Control	Via Ethernet or via RS-485 (RJ45)
Image Stabilizer	Yes
Video Output	1 Vpp composite output, 75 ohm
Network	
Ethernet	10/100 base - T x2 for LAN/WAN
Protocol Supported	TCP/IP, HTTP, ARP, PPPoE, DDNS, DHCP, RTP/RTSP
QoS	Layer 2, 3
Simultaneous Access	Unlimited (Multicast)
Connector	
Network	RJ45 x 2
Serial Port	RS-485
Analogue Video Output	BNC connector X 1 (NTSC/PAL)
Digital Input/Output	DI x 2, DO x 2
Reset	Reset x 1

Features:

Built-in web server and network interface.

CIF up to Full D1 resolution.

MPEG-4 ASP compliant hardware compression.

Compatible with most of worldwide SI systems.

Dual 10/100Base-T Ethernet ports for WAN & LAN.

Remote Pan/Tilt/Zoom control.

270X Zoom: 27X optical zoom and 10X digital zoom.

QoS enabled (L2, L3) for video streaming
(UniCast / MultiCast).

Bundle with 32 channel remote software.



Corner Mount

Pole Mount

Console